

SPECIFICATIONS

Model	POS-3000-AT	POS-3000-CD
Main Board		
CPU Support	Intel Atom N270 (1.6GHz, 512KB Cache)	Intel Celeron M 440 (1.86GHz, 1MB Cache) Intel Core Duo T2500 (2GHz, 2MB Cache) Intel Core 2 Duo T7400 (2.16GHz, 4MB Cache)
Chipset	Intel 82945GSE + 82801GBM(ICH7)	Intel 82945GME + 82801GBM(ICH7)
System Memory	1 x 200pin DDR2, up to 2GB	2 x 200pin DDR2, up to 4GB
Graphic Memory	Share System Memory 64~224MB	
BIOS	Award	
LCD Touch Panel		
LCD Size	15"	
Brightness	250nits	
Resolution	1024 x 768	
Touch Screen	5 wire Resistive or SAW	
Tilt Angle	0~90 Degree	
Storage		
HDD	1 x 2.5" SATA HDD Bay	
Flash Memory	1 x Compact Flash Slot (Type 1 & 2)	
Internal Expansion		
USB 2.0	1 x Touch, 1 x Wi-Fi	
Serial	1 x COM for Touch Option, 1 x COM Reserved, 1 x COM for MSR	
I/O Ports		
USB 2.0	4 x Bottom I/O, 2 x Left Side I/O	
Serial	2 x COM with Power Selected 5/12V on pin9, 1 x COM standard	
Parallel	1 x DB25	
PS2	1 x KB, 1 x MS on Left Side I/O	
LAN	1 x Giga LAN (Realtek 8111C)	2 x Giga LAN (Realtek 8111C)
2nd Display	1 x VGA, DB15	
Cash Drawer	1 x RJ11, Selected 12/24V	
DC In	1 x 4pin 12V, 7.5A	
DC Out	1 x 12V for Customer Display or 2nd Monitor	
Audio	1 x Line Out, 1 x Mic In, 2 x Internal Speaker 2W	
Power		
Power Adapter	Hidden Under the Base, 12V, 90W, w/ Cable Head Lock	
Indicator	1 x Power LED in Blue	
Optional Peripheral		
MSR	3 Track, PS2 or USB or COM	
Customer Display	VFD / LCD, Rear Mounted	
Wi-Fi	IEEE 802.11b/g, Pole Antenna	
Environment		
EMC & Safety	FCC & CE	
Operating Temp.	0 ~ 40°C	
Storage Temp.	-20 ~ 55°C	
Operate Humidity	20% ~ 80% RH non-condensing	
Storage Humidity	20% ~ 85% RH non-condensing	
Dimension (mm)	335 x 230 x 350 (W x D x H)	
Weight (kg)	7.3	
Support	POS Ready, XP Pro, Vista, Linux, Win7	

- Concealed Cable Routing
- Modern & Sleek Design
- Piano Gloss Finish
- Rich I/O Interface
- Easy Maintenance

Fametech Inc.

Your Reliable POS Solution Provider



Zenis POS

Featured POS Terminal Of The Year



[Http://www.fametech.com.tw](http://www.fametech.com.tw)

Manufacturer

FAMETECH INC.

2F, No. 165, Sec. 2, Ta-Tung Rd.,
Hsi-Chih 221, Taipei County, Taiwan
Tel : 886-2-8692-6300
Fax: 886-2-8692-6301
E-Mail: tyssso@ms6.hinet.net
URL: <http://www.fametech.com.tw>



Insist On The Best

Zenis POS

Revolutionize Your Experience With Innovative Technology

> *Intro*

Zenis POS is an epochal POS terminal that fulfills all your visual and functional demands. This much anticipated all-in-one POS system features sleek and stylish exterior with piano gloss finish, giving your counter a refreshing and elegant look. Its compact footprint saves valuable counter space and is ideal for situations where space is an issue. The touch screen monitor can be tilted from 5 to 90 degree, ensuring easy interactivity for users and delivers accurate input. Zenis POS comes with rich I/O ports (including 8 USB 2.0 and 3 Serial ports), which allow the users to have more flexibility to integrate their own peripherals with the terminal. It is also equipped with smart fan function, which automatically adjusts the fan speed of the processor depending on the temperature of the latter.



- Piano Gloss Painted, Comes In White, Black and Red
- Modularized and Sleek Exterior Design
- Replaceable Front Bezel
- Clean & Neat Cable Routing Design
- Four Different Grades of CPUs Selectable (Atom, Core-2-Duo, Core Duo, Celeron)



> *Images & Features*



Easy to Reach Side I/O Ports



With Second Display



Glossy Customer Display



With Rear Display



Power Adaptor Hidden Under Base



Concealed Cable Routing



Strong & Sturdy Aluminum Base



Efficient Heat Dissipation

Zenis POS